

SPECIFICATIONS

1704 2D scanner

RUGGED, VERSATILE



1704

1704DC (can capture A4 document)

Performance	Category	2D barcode scanner								
	Optical sensor	1280 (H) × 1024 (V)								
	Light source	Red LED 630 nm±20 nm								
	Resolution	5 mil 1D		6.67 mil 2D						
	Depth of field at 80% MRD	Code 39	5 mil	6.4 to 17.8 cm / 2.5 to 7 in.			Code 39	5 mil	10.7 to 25.4 cm / 4.2 to 10 in.	
		Code 39	7.5 mil	6.4 to 22.9 cm / 2.5 to 9 in.			Code 39	7.5 mil	6.4 to 36.3 cm / 2.5 to 14.3 in.	
		UPCA	13 mil	6.4 to 25.4 cm / 2.5 to 10 in.			UPCA	13 mil	6.4 to 41.4 cm / 2.5 to 16.3 in.	
		Code 39	20 mil	6.4 to 36.8 cm / 2.5 to 14.5 in.			Code 39	20 mil	7.1 to 58.4 cm / 2.8 to 23 in.	
		PDF 417	6.67 mil	7.6 to 17.3 cm / 3 to 6.8 in.			PDF 417	6.67 mil	12.2 to 24.9 cm / 4.8 to 9.8 in.	
		PDF 417	10 mil	7.6 to 19.8 cm / 3 to 7.8 in.			PDF 417	10 mil	10.2 to 32.3 cm / 4 to 12.7 in.	
	PDF 417	15 mil	11.9 to 23.6 cm / 4.7 to 9.3 in.			PDF 417	15 mil	11.9 to 38.9 cm / 4.7 to 15.3 in.		
	Scanning angle	Pitch ±65° Skew ±60°								
	PCS	Minimum 25%								
	Frame rate	30 frames/second								
Interfaces supported	RS232 / Keyboard wedge / USB HID / USB Virtual COM									
Barcodes supported	<i>1D symbology:</i> Codabar, Code 11, Code 39, Code 93, Code 128, Discrete 2 of 5, Interleaved 2 of 5, MSI, RSS, UPC/EAN, UPC/EAN128 <i>2D symbology:</i> Aztec and composites, DataMatrix, Maxicode, PDF417, QRCode <i>Postal codes:</i> Australia, Japan, U.S. Postnet, U.S. Planet, UK									
Programmable features	Data editing, multi-barcode editing, data format editing									
Language support	US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German, Japanese									
Physical	Weight including battery	306 g / 10.8 oz.								
	Color	Yellow								
	Switch	Tactile switch								
Electrical	Voltage	4.5 to 24V								
	Power consumption Standby / Operating	45mA / 378mA @5V								
User environment	Operating temperature	-10° to 55°C / 14° to 131°F ¹								
	Storage temperature	-40° to 70°C / -40° to 158°F								
	Humidity Non-condensing	Operating: 10% to 90% Storage: 5% to 95%								
	Impact resistance	1.8 m / 5.9 ft., five drops per side								
	Electrostatic discharge	±15 kV air discharge, ±8 kV contact discharge								
	Ingress protection	IP54								
	EMC regulation	BSMI, CE, C-Tick, FCC, IC								
Configuration	Setup options include Windows® based ScanMaster software by direct connection or printing out barcode settings									
Accessories	Power Hood									
Warranty	3 years / engine 1 year									



Power Hood

¹adapter's operating temperature is 0° to 40°C (32° to 104°F)

© 2011 CIPHERLAB Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.



HEADQUARTERS
 CIPHERLAB Co., Ltd.
 12F, 333 Dunhua S. Rd., Sec.2
 Taipei, Taiwan 10669
 Tel +886 2 8647 1166
 Fax +886 2 8732 3300
 www.cipherlab.com

CIPHERLAB China
 J Room, 4F, No.728 West Yan'an
 Road, Changning District, Shanghai
 China 200050
 Tel +86 21 3368 0288
 Fax +86 21 3368 0286

CIPHERLAB USA
 2552 Summit Avenue
 Plano, Texas USA 75074
 Tel +1 469 241 9779
 Toll Free 888 300 9779
 Fax +1 469 241 0697

CIPHERLAB Central Europe
 Willicher Damm 143-145
 41066 Mönchengladbach
 Germany
 Tel +49 2161 56230 0
 Fax +49 2161 56230 22