

MV-SC3050XM-S

5 MP Mono Vision Sensor



Introduction

With built-in high-precision vision algorithms, MV-SC3050XM-S vision sensor can realize counting, existence, measurement, recognition and other functions. It can be easily configured and operated via the SCMVS client software, and it uses RS-232 and Ethernet to output vision tool results and customized results.

Applicable Industry

Consumer electronics, food and pharmaceutical, automobile, etc.

Available Model

- 8 mm focal length:
MV-SC3050XM-08M-WBN-S
- 12 mm focal length:
MV-SC3050XM-12M-WBN-S
- 16 mm focal length:
MV-SC3050XM-16M-WBN-S

Key Features

- Adopts embedded hardware platform to realize high-speed image processing.
- Built-in high-precision positioning, measurement and recognition algorithms for counting, defects, existence, positioning and other functions.
- Adopts multiple IO interfaces for input and output signals.
- Supports viewing the device's status in real time via 360° visual indicator, convenient for debugging and maintenance.
- Adopts polarized, diffuser, and full-transparent multiple optical lighting with good environmental adaptability.
- Supports RS-232, TCP, UDP, FTP, Modbus, PROFINET, EtherNet/IP and other communication modes.

Specification

Model	MV-SC3050XM-08M-WBN-S	MV-SC3050XM-12M-WBN-S	MV-SC3050XM-16M-WBN-S
Tool			
Vision tool	<ul style="list-style-type: none">● Measurement: P2P measurement, P2L measurement, contrast measurement, grayscale size, edge width measurement, width measurement, brightness analysis, L2L angle, diameter measurement, and line angle● Existence: Spot existence, edge existence, contour existence, pattern existence, circle existence, line existence, anomaly judge, and existence detection● Count: Spot count, edge count, contour count, pattern count, and learning-based count● Recognition: Multi-object count, code recognition, category recognition, classification registration, object detection registration, and OCR● Logic: Calculator, If module, logic judge, format output, condition judge, character comparison, and combination judge● Location: Calibration convert, single point alignment, point rectify, point grasp, scale transformation, and fixture● Deep learning: DL classification and DL object detection● Defect detection: Anomaly detection		
Solution capacity	Supports importing and exporting project, up to 32 projects can be stored		
Communication protocol	RS-232, TCP, UDP, FTP, PROFINET, Modbus, EtherNet/IP, MELSEC/SLMP, FINS, Keyence KV		
Camera			
Sensor type	CMOS, global shutter		
Pixel size	3.45 μm × 3.45 μm		
Sensor size	1/1.45"		
Resolution	2432 × 2048		
Max. frame rate	40 fps		
Gain	0 dB to 15 dB		
Exposure time	6 μs to 1 sec		
Pixel format	Mono 8		
Mono/color	Mono		
Electrical feature			
Data interface	Fast Ethernet (100 Mbit/s)		
Digital I/O	17-pin M12 connector provides power and I/O, including opto-isolated input (LINE 0/1/2) × 3, opto-isolated output (LINE 3/4/5) × 3, and RS-232 × 1 Supports triggering device via pressing top trigger button		
Power supply	24 VDC		
Power consumption	Typ. 6.5 W @ 24 VDC		
Mechanical			
Lens mount	M12-mount, mechanical autofocus supported		
Focal length	8 mm	12 mm	16 mm
Lens cap	Polarized + diffuser + full-transparent lens cap		
Light source	White spot light source. Red/blue/IR point light source is optional		
Aiming system	1 LED		
Indicator	Multi-angle visual indicator		
Dimension	43 mm × 57 mm × 45.9 mm (1.7" × 2.2" × 1.8")		
Weight	Approx. 200 g (0.4 lb.)		


Specification

Model	MV-SC3050XM-08M-WBN-S	MV-SC3050XM-12M-WBN-S	MV-SC3050XM-16M-WBN-S
Ingress protection	IP65		
Temperature	Working temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: −30 °C to 70 °C (−22 °F to 158 °F)		
Humidity	20% RH to 95% RH (no condensation)		
General			
Client software	SCMVS		
Certification	CE, KC		

Detection Range

Lens focal length	Installation distance	Field of view	Single pixel accuracy
8 mm	25 mm	26.22 mm × 22.08 mm	0.011 mm
	2000 mm	2097.6 mm × 1766.4 mm	0.863 mm
12 mm	60 mm	41.95 mm × 35.33 mm	0.017 mm
	2000 mm	1398.4 mm × 1177.6 mm	0.575 mm
16 mm	100 mm	52.44 mm × 44.16 mm	0.022 mm
	2000 mm	1048.8 mm × 883.2 mm	0.431 mm


Horizontal Field of View/mm




Dimension

HIKROBOT

Device:



Installation Bracket:



Device and Installation Bracket:

